



Elo conector de cintas - Grau 8

FS 4:1

	Código	mm	CMT (t)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	Peso (kg)
	201.501	6	1,2	16	16	8	55	35	0,17
	201.502	8	2	20	21	10	61	35	0,29
	201.503	10	3,15	26	30	13	79	35	0,49
	201.504	13	5,4	30	30	17	90	46	1,06
	201.505	16	8	36	40	22	115	56	1,89
	201.506	18/20	12,5	44	47	23	130	65	3,20
	201.507	22	15	55	53	27	117	70	6,50
	201.508	26	21,2	58	60	32	207	150	10,40
	201.509	32	31,5	70	78	38	272	160	18,70


Elo conector de correntes - Grau 8 (Conforme EN 1677)

FS 4:1

	Código	mm	CMT (t)	A (mm)	B (mm)	C (mm)	D (mm)	Peso (kg)
	221.201	6	1,12	7	42	37	16	0,14
	221.202	8	2	8	58	48	20,5	0,21
	221.203	10	3,15	10,8	68	60	28	0,38
	221.204	13	5,3	15	90	76	30	0,76
	221.205	16	8	19,8	102	91	36,3	1,00
	221.206	18/20	12,5	24,7	121	109	44	1,90
	221.207	22	15	26	142	130	51	2,80


Elo Ômega - Grau 8

FS 4:1

	Código	mm	CMT (t)	K (mm)	D (mm)	T (mm)	P (mm)	Peso (kg)
	221.221	8	2	36	25	11	9	0,21
	221.222	10	3,15	40	32	15	12	0,42
	221.223	13	5,3	54	42	18	16	1,10
	221.224	16	8	66	50	24	18	1,42


Gancho olhal com trava - Grau 8

FS 4:1

	Código	mm	CMT (t)	A (mm)	B (mm)	C (mm)	L (mm)	H (mm)	I (mm)	Peso (kg)
	213.401	6	1,12	9	20	24	78	21	14	0,30
	213.402	8	2	11	25	30	97	24	16,5	0,50
	213.403	10	3,15	15	38	34	117	32,5	22	1,04
	213.404	13	5,3	19	43	39	149	44	27	2,15
	213.405	16	8	23	50	46	180	46	34	3,25
	213.406	18/20	12,5	24	62	48	215	61	42	6,36
	213.407	22	15	33	62	87	236	71	44	8,50
	213.408	26	21,2	35	62	97	276	84	60	13,00
	213.409	32	31,5	40	88	115	351	93	66	17,00

Gancho giratório olhal automático - Grau 8

FS 4:1

	Código	mm	CMT (t)	A (mm)	B (mm)	C (mm)	K (mm)	H (mm)	I (mm)	Peso (kg)
	212.401	6	1,12	150	33	23	28	21	14,5	0,71
	212.402	8	2	185	34	27	34	22	19,5	1,30
	212.403	10	3,15	216	42	35	45	31	22	2,10
	212.404	13	5,3	268	48	41	54	41	33	4,67
	212.405	16	8	330	61	54	62	52	37	7,33
	212.406	18/20	12,5	355	70	64	70	59	51	12,00

